

TYPE OR USE PEN
SELF TRANSCRIBING
PRESS HARD

WELL LOG AND DRILLING REPORT

Ohio Department of Natural Resources

Division of Water, 2045 Morse Road

Columbus, Ohio 43229-6605 Voice (614) 265-6740 Fax (614) 265-6767

1008693

WELL LOCATION

County FAIRFIELD Township LIBERTY
Owner/Builder Buy LAM
Address of Well Location 11051 SNYDER CHURCH RD.
City BALTIMORE OH Zip Code +4 43105
Permit No. 2007-147 Section/Lot No.
Location of Well in State Plane coordinates, if available: Use of Well DOMESTIC
N ☐ X +/- ft. or m
S ☐ Y +/- ft. or m
Elevation of Well 925' +/- ft. or m
Datum Plain: ☐ NAD27 ☐ NAD83 Elevation Source GPS
Source of Coordinates: ☒ GPS ☐ Survey ☐ OtherSketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: Lat: 39° 53.321' Long: West 082° 38.553'

204

1/10
SNYDER CH. RD.

STEMEN RD

South

WELL TEST*

Pre-Pumping Static Level 22 ft. Date 10-16-07
Measured from: ☐ Top of Casing ☒ Ground Level ☐ Other
☐ Air ☐ Bailing ☐ Pumping* ☐ Other
Test Rate 30 gpm Duration of Test 1 hrs.
Feet of Drawdown 0 ft. Sustainable Yield 30 gpm
*(Attach a copy of the pumping test record, per section 1521.05, ORC)
Is Copy Attached? ☐ Yes ☒ No Flowing Well? ☐ Yes ☐ No
Quality Clear

PUMP/PITLESS

Type of pump SUBMERSIBLE Capacity 1/2 HP gpm
Pump set at 35 ft. Pitless Type ADAPTER
Pump installed by R.C. BARRY

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm STAGE INC. DBA R.C. BARRY
Address 6531 W. BROAD ST
City, State, Zip GALLOWAY OH 43119Signed Darrin Caton #41 / MC Date 10-16-07
ODH Registration Number #368

CONSTRUCTION DETAILS

☒ Rotary ☐ Cable ☐ Augered ☐ Driven ☐ Other

BOREHOLE/CASING (measured from ground surface)

1 ☒ Borehole Diameter 7 7/8 inches Depth 39 ft.
Casing Diameter 5 in. Length 39 ft. Thickness SDR17 in.2 ☐ Borehole Diameter inches Depth ft.
Casing Diameter in. Length ft. Thickness in.Casing Height Above Ground 15" ft.Type 1 ☐ Steel 1 ☐ Galv. 1 ☒ PVC 1 ☐
2 ☐ Steel 2 ☐ Galv. 2 ☐ PVC 2 ☐ OtherJoints 1 ☐ Threaded 1 ☐ Welded 1 ☒ Solvent 1 ☐
2 ☐ Threaded 2 ☐ Welded 2 ☐ Solvent 2 ☐ Other

SCREEN

Diameter 5 Slot Size 50 Screen Length 2 ft.Type PVC Material PVCSet Between 37 ft. and 39 ft.

GRAVEL PACK (Filter Pack)

Material/Size #4 SAND Volume/Weight Used 400 #Method of Installation Depth: Placed FROM 35 ft. TO 39 ft.

GROUT

Material BENSEAL + EZMAD Volume/Weight Used 50 gal water / 100 #Method of Installation TKEMIE PIPEDepth: Placed FROM 35 ft. TO SURFACE ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation:
sandstone, shale, limestone, gravel, clay, sand, etc.

From To

GRAVELY CLAY
SAND + GRAVEL

0 29

29 39

Water encountered
at 39'

*(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion 10-16-07 Total Depth of Well 39 ft.Completion of this form is required by section 1521.05, Ohio Revised Code - file within 30 days after completion of drilling.
ORIGINAL COPY TO - ODNR, DIVISION OF WATER, 2045 MORSE ROAD, COLS., OHIO 43229-6605
Blue - Customer's copy Pink - Driller's copy Green - Local Health Dept. copy