

TYPE OR USE PEN
SELF TRANSCRIBING
PRESS HARD

Ohio Department of Natural Resources
Division of Soil and Water Resources, 2045 Morse Road Building B
Columbus, Ohio 43229-6693 Voice (614) 265-6740 Fax (614) 265-6767

County

Carroll

Township

Washington

Owner/Builder

John Baker

Address of Well Location

3160 Lunar Rd. N.E.

City

Carrollton Oh.

Zip Code +4

44615

Permit No.

582020

Section/Lot No.

Location of Well in State Plane coordinates, if available:

Use of Well

Home

N

X

ft. or m

S

Y

ft. or m

Elevation of Well

ft. or m

Datum Plain:

NAD27

NAD83

Elevation Source

Source of Coordinates:

GPS

Survey

Other

Sketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: Lat: 40.622942 Long: 81.05259

North

South

West

East

STAT 9

Cobblers Rd

Lunar

House

Pre-Pumping Static Level

130

ft.

Date

10-18-2020

Measured from:

Top of Casing

Ground Level

Other

Air

Bailing

Pumping*

Other

Test Rate

10

gpm

Duration of Test

1 1/2

hrs.

Feet of Drawdown

ft.

Sustainable Yield

10

gpm

Is Copy Attached?

Yes

No

Flowing Well?

Yes

No

Quality

Clear

PUMP/PITLESS

Type of pump

Submersible

Capacity

10

gpm

Pump set at

170

ft.

Pitless Type

PULL THRU

Pump installed by

Charles Smith

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm

Smitty's Drilling

Address

6141 BERMAN RD. SE

City, State, Zip

CARROLLTON OH. 44615

Signed

Charles P. Smith

Date

10-20-2020

ODH Registration Number

2420

CONSTRUCTION DETAILS

Rotary

Cable

Augered

Driven

Other

BOREHOLE/CASING

(measured from ground surface)

Borehole Diameter

8 1/2

inches

Depth

180

ft.

Casing Diameter

5

in.

Length

120 1/2

ft.

Thickness

21.5

in.

Borehole Diameter

inches

Depth

ft.

Casing Diameter

in.

Length

ft.

Thickness

in.

Casing Height Above Ground

1 1/2

ft.

Type

1

Steel

1

Galv.

1

PVC

1

Other

2

Steel

2

Galv.

2

PVC

2

Other

Joints

1

Threaded

1

Welded

1

Solvent

1

Other

2

Threaded

2

Welded

2

Solvent

2

Other

SCREEN

Diameter

5 1/4

Slot Size

3/8 Holes

Screen Length

60

ft.

Type

Holes

3/8

Material

21.5

in.

Set Between

120

ft.

and

180

ft.

GRAVEL PACK (Filter Pack)

Material/Size

Volume/Weight Used

Method of Installation

ft. TO

ft.

Depth: Placed FROM

ft. TO

ft.

GROUT

Material

Bentonite

Volume/Weight Used

22 GAL Per Bag 10 Bags

Method of Installation

Tremie Tube Pressure

Depth: Placed FROM

120

ft. TO

0

ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation: sandstone, shale, limestone, gravel, clay, sand, etc.

From

To

Topsoil

0

1

Shale Sandy Brown

1

18

Sandstone Grey Med

18

34

Shale Grey med

34

48

Shale DARK Grey HARD

48

73

Sandy Shale Broken

73

117

Sandstone Grey HARD

117

180

(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion

10-21-20

Total Depth of Well

180

ft.

Completion of this form is required by section 1521.05, Ohio Revised Code - file within 30 days after completion of drilling.

ORIGINAL COPY TO - ODNr, DIVISION OF SOIL AND WATER RESOURCES, 2045 MORSE ROAD BLD. B, COLS., OHIO 43229-6693

Blue - Customer's copy Pink - Driller's copy Green - Local Health Dept. copy