

WELL LOG AND DRILLING REPORT

Ohio Department of Natural Resources
Division of Water, 1939 Fountain Square Drive
Columbus, Ohio 43224-9971 Voice (614) 265-6739 Fax (614) 447-9503

857225

CountyGeaugaTownshipAuburn

Owner/BuilderAlanBegy

Address of Well Location18930Sanctuary Drive

CityAuburnZip Code +444355

Permit No.155655Section/Lot No.

Location of Well in State Plane coordinates, if available:

Use of WellHouse

N X S Y

Elevation of Well1187

Datum Plain: NAD27 NAD83

Source of Coordinates: GPS Survey Other

Sketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: Lat. 41.21012 Long. 81.15278

WELL TEST*

Pre-Pumping Static Level30 ft. Date12.5.05

Measured from: Top of Casing Ground Level Other

Air Bailing Pumping* Other

Test Rate20 gpm Duration of Test1/2 hrs.

Feet of Drawdown15 ft. Sustainable YieldYES gpm

*(Attach a copy of the pumping test record, per section 1521.05, ORC)

Is Copy Attached? Yes No Flowing Well? Yes No

QualityGood

PUMP/PITLESS

Type of pumpBaron Capacity12 gpm

Pump set at65 ft. Pitless TypeDickens

Pump installed byAction Well Drilling

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling FirmAction Well Drilling

Address7800 SR. 82

City, State, ZipGarrettsville, OH 44231

SignedJay Kelt Date12.5.05

ODH Registration Number25323

CONSTRUCTION DETAILS

Rotary Cable Augered Driven Other

BOREHOLE/CASING (measured from ground surface)

Borehole Diameter5 1/2 inches Depth88 ft.

Casing Diameter6 in. Length50 ft. Thickness188 in.

Borehole Diameter inches Depth ft.

Casing Diameter in. Length ft. Thickness in.

Casing Height Above Ground ft.

Type1 Steel 2 Galv. 1 PVC 1 Other

Joints1 Threaded 1 Welded 1 Solvent 1 Other

SCREEN

Diameter Slot Size Screen Length

Type Material

Set Between ft. and ft.

GRAVEL PACK (Filter Pack)

Material/Size Volume/Weight Used

Method of Installation

Depth: Placed FROM ft. TO ft.

GROUT

MaterialBen seal Volume/Weight Used2 8995

Method of InstallationDry Driven

Depth: Placed FROM50 ft. TOSurface ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation: sandstone, shale, limestone, gravel, clay, sand, etc.

	From	To
Clay + sand	0	40
Brown soft sand stone	40	50
sand stone	50	88

(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion12.5.05

Total Depth of Well88 ft.

Completion of this form is required by section 1521.05, Ohio Revised Code - file within 30 days after completion of drilling.
ORIGINAL COPY TO - ODNR, DIVISION OF WATER, 1939 FOUNTAIN SQ. DRIVE, COLS., OHIO 43224-9971
Blue - Customer's copy Pink - Driller's copy Green - Local Health Dept. copy