

WELL LOG AND DRILLING REPORT

Ohio Department of Natural Resources
Division of Water, 1939 Fountain Square Drive
Columbus, Ohio 43224-9971 Voice (614) 265-6739 Fax (614) 447-9503

874821

WELL LOCATION

County Holmes Township Knox

Owner/Builder Jeff McIlor

Address of Well Location 6005 SR 514

City Lakaville Ohio Zip Code +4 44638 +4

Permit No. 125528-99

Location of Well in State Plane coordinates, if available:

Datum Plain: ☐ NAD27 ☐ NAD83 Elevation Source

Source of Coordinates: ☐ GPS ☐ Survey ☐ Other

Sketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: Lat: Long:

West

East

South

WELL TEST*

Pre-Pumping Static Level 70 ft. Date 4/20/99

Measured from: ☒ Top of Casing ☐ Ground Level ☐ Other

☐ Air ☒ Bailing ☐ Pumping* ☐ Other

Test Rate 20 gpm Duration of Test 1 hrs.

Feel of Drawdown 0 ft. Sustainable Yield 10 gpm

*(Attach a copy of the pumping test record, per section 1521.05, ORC)

Is Copy Attached? ☐ Yes ☒ No Flowing Well? ☐ Yes ☒ No

Quality clear

PUMP/PITLESS

Type of pump Subm. Capacity 10 gpm

Pump set at 208 ft. Pitless Type Bulldog

Pump installed by Moravy Drilling

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm Moravy Drilling

Address 8036 8042 T.R. 314

City, State, Zip Holmesville Ohio 44633

Signed Janella Moravy Date

ODH Registration Number 233

CONSTRUCTION DETAILS

☐ Rotary ☒ Cable ☐ Augered ☐ Driven ☐ Other

BOREHOLE/CASING (measured from ground surface)

1 ☐ Borehole Diameter 5 inches Depth 130 ft.

Casing Diameter 5 in. Length 118 ft. Thickness 0.215 in.

2 ☐ Borehole Diameter inches Depth ft.

Casing Diameter in. Length ft. Thickness in.

Casing-Height Above Ground 2 ft.

Type ☒ Steel ☐ Galv. ☐ PVC ☐ Other

2 ☐ Steel ☐ Galv. ☐ PVC ☐ Other

Joints ☒ Threaded ☐ Welded ☐ Solvent ☐ Other

2 ☐ Threaded ☐ Welded ☐ Solvent ☐ Other

SCREEN

Diameter Slot Size Screen Length ft.

Type Material

Set Between ft. and ft.

GRAVEL PACK (Filler Pack)

Material/Size Volume/Weight Used

Method of Installation

Depth: Placed FROM ft. TO ft.

GROUT

Material Volume/Weight Used

Method of Installation

Depth: Placed FROM ft. TO ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation: sandstone, shale, limestone, gravel, clay, sand, etc.

	From	To
Brown Clay	0	10
Gumbo	10	33
Mud + Gravel	33	68
Broken Sandstone	68	120
Br + Gr Sandstone	120	130

water ab. 120'

Total Depth 130

*(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion 4/20/99 Total Depth of Well 130 ft.