

TYPE OR USE PEN
SELF TRANSCRIBING
PRESS HARD

WELL LOG AND DRILLING REPORT

Ohio Department of Natural Resources
Division of Water, 1939 Fountain Square Drive
Columbus, Ohio 43224-9971 Voice (614) 265-6740 Fax (614) 265-6767

982186

WELL LOCATION

CONSTRUCTION DETAILS

County Muskingum Township HopewellOwner/Builder Jennifer Lewis
(Circle One or Both) First LastAddress of Well Location 1955 Flint Ridge Rd
Number Street NameCity Hopewell Zip Code +4 43746Permit No. 370961 Section/Lot No.
(Circle One or Both)Location of Well in State Plane
coordinates, if available:N ☒ X +/- ft. or mS ☐ Y +/- ft. or mElevation of Well 1086 +/- ft. or mDatum Plain: ☐ NAD27 ☐ NAD83 Elevation Source Source of Coordinates: ☐ GPS ☐ Survey ☐ Other TraverseSketch a map showing distance well lies from numbered state highways, street
intersections, county roads, buildings or other notable landmarks. Latitude and
longitude are available please include here: Lat: 39.135 Long: -81.9818

WELL TEST*

Pre-Pumping Static Level 286 ft. Date
Measured from: ☐ Top of Casing ☒ Ground Level ☐ Other
☐ Air ☒ Bailing ☐ Pumping* ☐ Other
Test Rate 10 gpm Duration of Test 2 hrs.
Feet of Drawdown 35 ft. Sustainable Yield gpm

*(Attach a copy of the pumping test record, per section 1521.05, ORC)

Is Copy Attached? ☐ Yes ☒ No Flowing Well? ☒ Yes ☐ NoQuality good

PUMP/PITLESS

Type of pump Red Jacket Capacity 8 gpm
Pump set at 460 ft. Pitless Type Merrill
Pump installed by Dean Fulmer

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm Dean FulmerAddress 9440 Macedonia RdCity, State, Zip Hopewell, OhioSigned Nancy Fulmer Date ODH Registration Number 298Rotary ☐ Cable ☐ Augered ☐ Driven ☐ Other

BOREHOLE/CASING (measured from ground surface)

1 Borehole Diameter 8 inches Depth 440 ft.Casing Diameter in. Length ft. Thickness in.2 Borehole Diameter 7 inches Depth 498 ft.Casing Diameter 7 in. Length 500 ft. Thickness 3/8 in.Casing Height Above Ground 0 feetType 1 ☐ Steel 1 ☐ Galv. 1 ☐ PVC 1 ☐2 ☐ Steel 2 ☐ Galv. 2 ☐ PVC 2 ☐ Other Joints 1 ☐ Threaded 1 ☐ Welded 1 ☒ Solvent 1 ☐2 ☐ Threaded 2 ☐ Welded 2 ☐ Solvent 2 ☐ Other

SCREEN

Diameter Slot Size Screen Length ft.Type Material Set Between ft. and ft.

GRAVEL PACK (Filter Pack)

Material/Size Volume/Weight Used Method of Installation Depth: Placed FROM ft. TO ft.

GROUT

Material Benson Volume/Weight Used 47 bags 2050Method of Installation GroutDepth: Placed FROM 483 ft. TO Surface ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation:
sandstone, shale, limestone, gravel, clay, sand, etc.

	From	To
Gray Shale	255	258
Sandier Shale	258	263
Gray Shale	263	296
Sandier Shale	296	332
Gray Shale	332	456
Sandier Shale	456	486
Sand	486	498

drilled deeper

*(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion Total Depth of Well 498 ft.Completion of this form is required by section 1521.05, Ohio Revised Code - file within 30 days after completion of drilling.
ORIGINAL COPY TO - ODNR, DIVISION OF WATER, 1939 FOUNTAIN SQ. DRIVE, COLS., OHIO 43224-9971
Blue - Customer's copy Pink - Driller's copy Green - Local Health Dept. copy