

TYPE OR USE PEN
SELF TRANSCRIBING
PRESS HARD**WELL LOG AND DRILLING REPORT**Ohio Department of Natural Resources
Division of Water, 1939 Fountain Square Drive
Columbus, Ohio 43224-9971 Voice (614) 265-6740 Fax (614) 265-6767

984607

WELL LOCATION

County Medina Township Sharon

Owner/Builder WS Domes
(Circle One or Both) First Last

Address of Well Location 737 Messina Dr.
Number Street Name

City Medina Zip Code +4 44256

Permit No. 2530 Section/Lot No. -
(Circle One or Both)

Location of Well in State Plane coordinates, if available:
N 41.04.10 . 910 +/- 500 ft or m
S 81.54.8 . 050 +/- 500 ft or m
Elevation of Well 1000 . 00 +/- 500 ft or m
Datum Plain: ☒ NAD27 ☐ NAD83 Elevation Source
Source of Coordinates: ☒ GPS ☐ Survey ☐ Other

Sketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: Lat: 40 Long: 81
North

West

State

South

WELL TEST*

Pre-Pumping Static Level 30 ft. Date 5/7/05

Measured from: ☐ Top of Casing ☒ Ground Level ☐ Other

☐ Air ☒ Bailing ☐ Pumping* ☐ Other

Test Rate 18 gpm Duration of Test 1 hrs.

Feet of Drawdown 10 ft. Sustainable Yield 18 gpm

*(Attach a copy of the pumping test record, per section 1521.05, ORC)

Is Copy Attached? ☐ Yes ☒ No Flowing Well? ☐ Yes ☒ No

Quality

PUMP/PITLESS

Type of pump Capacity gpm

Pump set at ft. Pitless Type

Pump installed by Crowley

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm Neug Adams Well Drilling

Address 1174 Mt Pleasant Rd

City, State, Zip N Canton OH 44720

Signed Neug Adams Date 5/7/05

ODH Registration Number 395

CONSTRUCTION DETAILS

☐ Rotary ☒ Cable ☐ Augered ☐ Driven ☐ Other

BOREHOLE/CASING (measured from ground surface)

1 Borehole Diameter 5 inches Depth 100 ft.
Casing Diameter 5 in. Length 31.4 ft. Thickness .250 in.

2 Borehole Diameter inches Depth ft.
Casing Diameter in. Length ft. Thickness in.

Casing Height Above Ground 2 ft.

Type 1 ☒ Steel 1 ☐ Galv. 1 ☐ PVC 1 ☐ Other
2 ☐ Steel 2 ☐ Galv. 2 ☐ PVC 2 ☐ Other

Joints 1 ☒ Threaded 1 ☐ Welded 1 ☐ Solvent 1 ☐ Other
2 ☐ Threaded 2 ☐ Welded 2 ☐ Solvent 2 ☐ Other

SCREEN

Diameter Slot Size Screen Length ft.

Type Material

Set Between ft. and ft.

GRAVEL PACK (Filter Pack)

Material/Size Volume/Weight Used

Method of Installation

Depth: Placed FROM ft. TO ft.

GROUT

Material Benseal Volume/Weight Used 1.5 bags/50#

Method of Installation dry down

Depth: Placed FROM 28.6 ft. TO 91 ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation:
sandstone, shale, limestone, gravel, clay, sand, etc.Clay
sandstone

From	To
0	29
29	100

*(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion 5/7/05 Total Depth of Well 100 ft.