

TYPE OR USE PEN
SELF TRANSCRIBING
PRESS HARD

WELL LOG AND DRILLING REPORT

Ohio Department of Natural Resources

Division of Water, 2045 Morse Road

Columbus, Ohio 43229-6605 Voice (614) 265-6740 Fax (614) 265-6767

0999010

WELL LOCATION

CONSTRUCTION DETAILS

County SUMMIT Township BATHOwner/Builder MR LOCKER
(Circle One or Both) First LastAddress of Well Location 4511 RANCHWOOD RD
Number Street NameCity BATH Zip Code +4 44333Permit No. 376044 Section/Lot No.
(Circle One or Both)Location of Well in State Plane coordinates, if available: Use of Well FAMILYN ☐ X +/- ft. or mS ☐ Y +/- ft. or mElevation of Well +/- ft. or mDatum Plain: ☐ NAD27 ☐ NAD83 Elevation Source Source of Coordinates: ☐ GPS ☐ Survey ☐ Other Sketch a map showing distance well lies from numbered state highways, street intersections, county roads, buildings or other notable landmarks. If latitude and longitude are available please include here: 41° 03.462 Lat 081° 35.789 Long
North

West

House

Well

SEPTIC TANK

DRIVE WAY

RANCHWOOD RD

South

WELL TEST*

Pre-Pumping Static Level 65 ft. Date 10-7-06Measured from: ☐ Top of Casing ☒ Ground Level ☐ Other ☐ Air ☒ Bailing ☐ Pumping* ☐ Other Test Rate 15 gpm Duration of Test 2 hrs.Feet of Drawdown 10 ft. Sustainable Yield 15 gpm

*(Attach a copy of the pumping test record, per section 1521.05, ORC)

Is Copy Attached? ☐ Yes ☐ No Flowing Well? ☐ Yes ☐ NoQuality CLEAR

PUMP/PITLESS

Type of pump 1/2" submersible Capacity 10 gpmPump set at 85' ft. Pitless Type Clay CasePump installed by Tom McNeill 1008

I hereby certify the information given is accurate and correct to the best of my knowledge.

Drilling Firm Town & Country Well & PumpAddress 4034 Manchester Rd.City, State, Zip Akron OH 44311Signed Tom McNeill Date 10/17/06ODH Registration Number 1028☐ Rotary ☒ Cable ☐ Augered ☐ Driven ☐ Other

BOREHOLE/CASING (measured from ground surface)

1 ☒ Borehole Diameter 5 inches Depth 100 ft.Casing Diameter 5 1/2 in. Length 44 ft. Thickness .277 in.2 ☐ Borehole Diameter inches Depth ft.Casing Diameter in. Length ft. Thickness in.Casing Height Above Ground 1 1/2 ft.Type 1 ☒ Steel 1 ☐ Galv. 1 ☐ PVC 1 ☐2 ☐ 2 ☐ 2 ☐ 2 ☐ Other Joints 1 ☒ Threaded 1 ☐ Welded 1 ☐ Solvent 1 ☐2 ☐ 2 ☐ 2 ☐ 2 ☐ Other

SCREEN

Diameter Slot Size Screen Length ft.Type Material Set Between ft. and ft.

GRAVEL PACK (Filter Pack)

Material/Size Volume/Weight Used Method of Installation Depth: Placed FROM ft. TO ft.

GROUT

Material BEATONITE Volume/Weight Used 100Method of Installation DRY RIVERDepth: Placed FROM 0 ft. TO 44 ft.

DRILLING LOG*

INDICATE DEPTH(S) AT WHICH WATER IS ENCOUNTERED.

Show color, texture, hardness, and formation: sandstone, shale, limestone, gravel, clay, sand, etc.	From	To
YELLOW CLAY & ROCKS	0	24
HARD PAN BANK RUN	24	32
BLUE CLAY & GRAVEL	32	40
YELLOW SANDSTONE	40	83
WHITE SANDSTONE	83	100

WATER AT 90 FT

*(If more space is needed to complete drilling log, use next consecutively numbered form.)

Date of Well Completion 10-7-06 Total Depth of Well 100 ft.

Completion of this form is required by section 1521.05, Ohio Revised Code - file within 30 days after completion of drilling.
ORIGINAL COPY TO - ODNR, DIVISION OF WATER, 2045 MORSE ROAD, COLS., OHIO 43229-6605
Blue - Customer's copy Pink - Driller's copy Green - Local Health Dept. copy